

TWK-270S

 Online
video
adviser
**Item No.: TWK-270S**

Fully equipped with a one-way valve, adjustable pressure switch with ON / OFF switch, and motor start load protection. Safety valve, pressure gauge, ball valve and condense water drain plug, including airtank certificate

 Product
video


TWK-200L

**Item No.: TWK-200L**

Fully equipped with a one-way valve, adjustable pressure switch with ON / OFF switch, and motor start load protection. Safety valve, pressure gauge, ball valve and condense water drain plug. Convenient wheels for mobile use, including air tank certificate.

 Product
video


TWK-270L / TWK-500L


**Item No.: TWK-270L (270 L) | TWK-500L (500 L)**

Fully equipped with a one-way valve, adjustable pressure switch with ON / OFF switch, and motor start load protection. Safety valve, pressure gauge, ball valve and condense water drain plug, including air tank certificate.


 Product
video
TWK-270L

 Product
video
TWK-500L


TWK-500SL

**Item No.: TWK-500SL**

Fully equipped with a one-way valve, adjustable pressure switch with ON / OFF switch, and motor start load protection. Safety valve, pressure gauge, ball valve and condense water drain plug, including air tank certificate. Control unit (with power saving star circuit function, electronic monitoring of pressure and temperature, automatic notification of service intervals, possible remote control of the compressor, protection and auto emergency shut down.

 Product
video


	TWK-270S (upright)	TWK-270L (horizontal)	TWK-500L (horizontal)	TWK-500SL (horizontal)	TWK-200L (horizontal)
Tank	270 Liter	270 Liter	500 Liter	500 Liter	200 Liter
Suction capacity	880 L / min.	880 L / min.	880 L / min.	1000 L / min.	420 L / min.
Working pressure	10 bar	10 bar	10 bar	10 bar	10 bar
Engine speed	1040 U/min.	1040 U/min.	1040 U/min.	-	1280 U/min.
Power	5,5 kW	5,5 kW	5,5 kW	7,5 kW	2,2 kW
Power supply..	400 V	400 V	400 V	400 V	230 V
Weight (approx.)	195 kg	195 kg	255 kg	460 kg	126 kg